

Pneumatically operated valve metric

Without feather.

Piston operated angle valve with changeable seat. The actuators can be stacked if required.

pipe	DN	DN fitting	nominal pressure PN	connection	part number				
∅	[mm]	[mm]	[bar]	A	60°	120°			
3/16"	0,6	1,6	14.000	M16x1,5		4MF1-14000-PNB			
1/4"	2,3	2,5	4.200		4MV2-04200-PNB	4MF2-04200-PNB			
	1,6	2,0	7.000		4MV2-07000-PNB	4MF2-07000-PNB			
	1,0	2,0	10.000			4MF2-10000-PNB			
3/8"	3,2	4,0	4.200	M20x1,5	4MV3-04200-PNB	4MF3-04200-PNB			
	1,6	2,0	7.000		4MV3-07000-PNB	4MF3-07000-PNB			
	1,6	2,0	10.000			4MF3-10000-PNB			
9/16"	8,0	9,0	2.500	M30x2	4MV4-02500-PNB	4MF4-02500-PNB			
	4,8	6,4	4.200		4MV4-04200-PNB	4MF4-04200-PNB			
3/4"	11,0	12,5	1.400						
	3,2	4,0	12.000						
	1,6	2,0	14.000						
1"	14,3	15,0	1.400						
	11,0	12,5	2.100						
	6,4	6,4	7.000						
30 mm	10,0	12,0	4.200				M42x2		4MF7-04200-PNB
1 1/2"	23,8	25,0	1.000						
	12,7	14,0	3.500						

