

Pneumatic pumps 657 – D2 series

Double acting pump, plunger diameter is 160 mm.

part number	transmission ratio	pressure		flow	connection		
		7 bar driven	8 Bar driven	l/min	air	inlet	outlet
657-D2-0032	4:1	28	32	54,00	G1/2	1/2" NPT	1/2" NPT
657-D2-0048	6:1	42	48	48,60	G1/2	1/2" NPT	1/2" NPT
657-D2-0080	10:1	70	80	30,61	G1/2	1/2" NPT	1/2" NPT
657-D2-0128	16:1	112	128	19,73	G1/2	1/2" NPT	1/2" NPT
657-D2-0224	28:1	196	224	11,30	G1/2	1/2" NPT	1/2" NPT
657-D2-0320	40:1	280	320	7,69	G1/2	1/2" NPT	1/2" NPT
657-D2-0512	64:1	448	512	4,94	G1/2	1/2" NPT	3/8" NPT
657-D2-0640	80:1	560	640	3,96	G1/2	1/2" NPT	3/8" NPT
657-D2-0800	100:1	700	800	3,13	G1/2	1/2" NPT	3/8" NPT
657-D2-1040	130:1	910	1040	2,40	G1/2	1/2" NPT	3/8" NPT
657-D2-1400	175:1	1225	1400	1,81	G1/2	3/8" NPT	9/16"-18 UNF
657-D2-2040	255:1	1785	2040	1,23	G1/2	1/4" NPT	9/16"-18 UNF
657-D2-3200	400:1	2800	3200	0,79	G1/2	1/4" NPT	9/16"-18 UNF

