

## Pneumatic pumps 657 – E1 Serie

Single acting pump, plunger diameter is 160 mm.

part number	transmission ratio	pressure		flow	connection		
		7 bar driven	8 bar driven	l/min	air	inlet	outlet
657-E1-0032	4:1	28	32	32,1	G1/2	1/2" NPT	1/2" NPT
657-E1-0048	6:1	42	48	29,91	G1/2	1/2" NPT	1/2" NPT
657-E1-0080	10:1	70	80	18,84	G1/2	1/2" NPT	1/2" NPT
657-E1-0128	16:1	112	128	12,42	G1/2	1/2" NPT	1/2" NPT
657-E1-0224	28:1	196	224	7,11	G1/2	1/2" NPT	3/8" NPT
657-E1-0320	40:1	280	320	4,89	G1/2	1/2" NPT	3/8" NPT
657-E1-0512	64:1	448	512	3,08	G1/2	1/2" NPT	3/8" NPT
657-E1-0640	80:1	560	640	2,44	G1/2	1/2" NPT	3/8" NPT
657-E1-0800	100:1	700	800	1,92	G1/2	1/2" NPT	3/8" NPT
657-E1-1040	130:1	910	1040	1,47	G1/2	1/2" NPT	3/8" NPT
657-E1-1400	175:1	1225	1400	1,14	G1/2	1/2" NPT	9/16"-18 UNF
657-E1-2040	255:1	1785	2040	0,75	G1/2	1/4" NPT	9/16"-18 UNF
657-E1-3200	400:1	2800	3200	0,48	G1/2	1/4" NPT	9/16"-18 UNF

