

Rückschlagventile metrisch

Gerade, elastischer Sitz (A wie B).

Normaler Öffnungsdruck der Rückschlagventile ist 2 bar.

Rohr ∅	DN [mm]	DN Fitting [mm]	Nenndruck PN [bar]	Anschluss A/B	Bestell-Nr.	
					60°	120°
3/16"	0,6	1,6	14.000	M16x1,5		4MF1-14000-16-S
1/4"	2,3	2,5	4.200		4MV2-04200-16-S	4MF2-04200-16-S
	1,6	2,0	7.000		4MV2-07000-16-S	4MF2-07000-16-S
	1,0	2,0	10.000			4MF2-10000-16-S
3/8"	3,2	4,0	4.200	M20x1,5	4MV3-04200-16-S	4MF3-04200-16-S
	1,6	2,0	7.000		4MV3-07000-16-S	4MF3-07000-16-S
	1,6	2,0	10.000			4MF3-10000-16-S
9/16"	8,0	9,0	2.500	M30x2	4MV4-02500-16-S	4MF4-02500-16-S
	4,8	6,4	4.200		4MV4-04200-16-S	4MF4-04200-16-S
3/4"	11,0	12,5	1.400			
	3,2	4,0	12.000			
	1,6	2,0	14.000			
1"	14,3	15,0	1.400			
	11,0	12,5	2.100			
	6,4	6,4	7.000			
30 mm	10,0	12,0	4.200	M42x2		4MF7-04200-16-S
1 1/2"	23,8	25,0	1.000			
	12,7	14,0	3.500			

