

Überdruckventile metrisch

Überdruckventile können auf einen Öffnungsdruck voreingestellt und abgenommen werden.

| Rohr ∅ | Anschluss A/B | Öffnungsdruck [bar] | Bestell-Nr. | |
|-----------|------------------|------------------------|----------------|----------------|
| | | | 60° | 120° |
| 1/4" | M16x1,5 | 250-700 | 4MV2-00700-7-S | 4MF2-00700-7-S |
| | | 700-2.000 | 4MV2-02000-7-S | 4MF2-02000-7-S |
| | | 1.000-3.000 | 4MV2-03000-7-S | 4MF2-03000-7-S |
| | | 1.500-5.000 | 4MV2-05000-7-S | 4MF2-05000-7-S |
| | | 3.000-8.000 | 4MV2-08000-7-S | 4MF2-08000-7-S |
| 3/8" | M20x1,5 | 250-700 | 4MV3-00700-7-S | 4MF3-00700-7-S |
| | | 700-2.000 | 4MV3-02000-7-S | 4MF3-02000-7-S |
| | | 1.000-3.000 | 4MV3-03000-7-S | 4MF3-03000-7-S |
| | | 1.500-5.000 | 4MV3-05000-7-S | 4MF3-05000-7-S |
| | | 3.000-8.000 | 4MV3-08000-7-S | 4MF3-08000-7-S |
| 9/16" | M30x2 | 250-700 | 4MV4-00700-7-S | 4MF4-00700-7-S |
| | | 700-2.000 | 4MV4-02000-7-S | 4MF4-02000-7-S |
| | | 1.000-3.000 | 4MV4-03000-7-S | 4MF4-03000-7-S |
| | | 1.500-5.000 | 4MV4-05000-7-S | 4MF4-05000-7-S |
| | | 3.000-8.000 | 4MV4-08000-7-S | 4MF4-08000-7-S |

